



BRA-168 DIP SWITCHES SETTING : 1

Supported bill R\$ 1(old,new), 2, 5, 10(old,new), 20, 50 6bills.

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★	1 Pulse / R\$ 1	OFF	OFF								
	2 Pulse / R\$ 1	OFF	ON								
	4 Pulse / R\$ 1	ON	OFF								
	10 Pulse / R\$ 1	ON	ON								
	Output Pulse <small>Lo= 50ms Hi=100ms</small>			OFF	OFF						
	Output Pulse <small>Lo=150ms Hi=100ms</small>			OFF	ON						
	Output Pulse <small>Lo= 20ms Hi=100ms</small>			ON	OFF						
	Output Pulse <small>Lo= 30ms Hi=100ms</small>			ON	ON						
	Inhibit level Active Low					ON					
★	Inhibit level Active High					OFF					
★	Accept R\$ 1(old,new)						ON				
	Reject R\$ 1(old,new)						OFF				
★	Accept R\$ 2							ON			
	Reject R\$ 2							OFF			
★	Accept R\$ 5								ON		
	Reject R\$ 5								OFF		
★	Accept R\$ 10(old,new)									ON	
	Reject R\$ 10(old,new)									OFF	
★	Accept R\$ 20 & 50										ON
	Reject R\$ 20 & 50										OFF

★ Manufacture setting

Note: (1)Please reset the bill acceptor after set the dip switch.

(2)Dip switches 1 to 5 are only used for pulse protocol.

DIP SWITCHES SETTING : 2

	FUNCTION	SW1	SW2	SW3	SW4
★	Pulse Normal High	ON			
	Pulse Normal Low	OFF			
	Pulse Protocol		ON		
	Protocol		OFF		
	HOLD			ON	
				OFF	
					ON
					OFF

